



Screwless Connectors Block Connectors

930-00/ 9

Order Info

| | |
|-----------------------------|---------------|
| reference number (ref. no.) | 112009 |
| PU | 300 |
| EAN | 4028012127382 |



Type

| | |
|-----------------|------------------------------------|
| Type | terminal block without release key |
| connection type | push-in |
| number of poles | 9 pole |
| colour | white |

Electrical Data

| | |
|---------------|-------|
| rated voltage | 450 V |
| rated current | 24 A |

Connection Data

| | |
|----------------------------|---------------------------|
| cross-section rating | 2.5 mm ² |
| cross-section rating (UL) | 20-14 AWG |
| clamping range internal | 0.5 - 2.5 mm ² |
| clamping range external | 0.5 - 2.5 mm ² |
| type of conductor internal | solid |
| type of conductor external | solid |
| stripping length | 8.0 - 9.0 mm |
| clamping units per pole | 2 |

Ambient Conditions

| | |
|---|-------|
| T _{max} ambient air (at rated current) | 85 °C |
|---|-------|

Materials

| | |
|-----------------------------------|-------|
| insulator material | PA |
| contact material | brass |
| flammability rating acc. to UL 94 | V-2 |

Approvals

| | |
|------------------|-----|
| acc. to EN 60998 | yes |
|------------------|-----|

acc. to UL yes

acc. to CSA yes
