



## Screw Terminal Blocks

### 230/ 1 HT

#### Order Info

reference number (ref. no.)	121241
PU	1,000
EAN	4028012139330



#### Type

Type	Terminal Block
connection type	screw
number of poles	1 pole
colour	brown

#### Electrical Data

rated voltage	450 V
rated current	24 A

#### Connection Data

cross-section rating	2.5 mm <sup>2</sup>
cross-section rating (UL)	22-12 AWG
clamping range	0.5 - 7.0 mm <sup>2</sup>
type of conductor	fine stranded, stranded, solid
stripping length	5.0 - 5.5 mm
fixing	Screw
clamping units per pole	1
contact screw assembly	0.8 x 4.0 / $\cup$ 0.5 Nm
socket diameter	3.10 mm
pin spacing	8.0 mm

#### Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	130 °C
T <sub>min</sub> ambient air (operation)	-40 °C

#### Materials

insulator material	PA HT
contact material	brass
flammability rating acc. to UL 94	V-0

## Approvals

<b>acc. to EN 60998</b>	yes
<b>acc. to UL</b>	yes
<b>acc. to CSA</b>	yes

## Accessories

<b>ZEL 110</b>	196420
----------------	--------