



## Building Installation Connector System AC 166®

G

Plug and Socket Connectors Flat Version

### AC 166 GBUPF/ 3 SW



#### Order Info

reference number (ref. no.)	165563
PU	200
EAN	4028012107261

#### Type

Type	socket
connection type	push-in
number of poles	3 pole
coding	1 (mains)
colour	black
protection against incorrect plugging	yes
PE-function	yes
strain relief	yes

#### Electrical Data

rated voltage	250 V
rated current	20 A
rated impulse voltage	4.0 kV

#### Connection Data

cross-section rating	2.5 mm <sup>2</sup>
cross-section rating (UL)	14 AWG
clamping range	0.5 - 2.5 mm <sup>2</sup>
sheathing cable diameter	7.5 - 10.5 mm
type of conductor	solid
stripping length	9.0 mm
dismantling length	35.0 mm
dismantling length PE	42.0 mm
clamping units per pole	2
strain relief assembly	PZ 1 / ⤵ 0.5 Nm

#### Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	70 °C
---	-------

<b>T<sub>max</sub> component (operation)</b>	110 °C
<b>T<sub>min</sub> component (operation)</b>	-20 °C
<b>IP Code acc. to EN 60529</b>	IP20
<b>IP Code when plugged</b>	IP40

## Materials

<b>insulator material</b>	PA
<b>contact material</b>	spring steel, brass
<b>flammability rating acc. to UL 94</b>	V-2

## Approvals

<b>acc. to EN 61535</b>	yes
<b>acc. to UL</b>	yes

## Accessories

<b>AC 166 VSF SW</b>	169563
<b>AC 166 VSF WS</b>	169553