



Circular Terminal Blocks IP68  
Circular Terminal Blocks AC 180 basic

AC 180 SKG-I D24

Order Info

reference number (ref. no.)	19077
PU	200
EAN	4028012122912



Type

Type	I-housing
colour	black

Connection Data

sheathing cable diameter	7.0 - 13.5 mm
--------------------------	---------------

Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	125 °C
T <sub>max</sub> component (operation)	125 °C
T <sub>min</sub> component (operation)	-40 °C
IP Code acc. to EN 60529	IP68

Materials

insulator material	PA
flammability rating acc. to UL 94	V-2

Approvals

Accessories

AC 180 SK/ 2 SL	19057
AC 180 SK/ 3 SL	19066
AC 180 SK/ 3+3 SL	19058
AC 180 SK/ 4 SL	19069
AC 180 SK/ 5 SL	19074
AC 180 SK/ 6 SL	19076
AC 169 WKZ SW21/24	749960
DR 16 RH	729011
DR 16 GS	729032

<b>DR 16 1x14,0</b>	729031
<b>DR 16 1x4,0</b>	729033
<b>DR 16 1x6,5</b>	729034
<b>DR 16 2x4,0</b>	729035
<b>DR 16 2x5,5</b>	729036
<b>DR 16 3x4,0</b>	729037
<b>DR 16 4x3,5</b>	729038
<b>DR 16 5x3,5</b>	729009