



Circular Terminal Blocks IP68  
Circular Terminal Blocks AC 180 basic  
**AC 180 SKG-Y D24 D29**



### Order Info

reference number (ref. no.)	19082
PU	100
EAN	4028012167425

### Type

Type	Y-housing
colour	black

### Connection Data

sheathing cable diameter	- 17.0 mm
--------------------------	-----------

### Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	85 °C
T <sub>max</sub> component (operation)	125 °C
T <sub>min</sub> component (operation)	-40 °C
IP Code acc. to EN 60529	IP68

### Materials

insulator material	PA
flammability rating acc. to UL 94	V-2

### Approvals

### Accessories

AC 180 SK/ 2 SL	19057
AC 180 SK/ 3 SL	19066
AC 180 SK/ 3+3 SL	19058
AC 180 SK/ 4 SL	19069
AC 180 SK/ 5 SL	19074
AC 180 SK/ 6 SL	19076
AC 169 WKZ SW21/24	749960
DR 16 RH	729011
DR 16 GS	729032
DR 16 1x14,0	729031

<b>DR 16 1x4,0</b>	729033
<b>DR 16 1x6,5</b>	729034
<b>DR 16 2x4,0</b>	729035
<b>DR 16 2x5,5</b>	729036
<b>DR 16 3x4,0</b>	729037
<b>DR 16 4x3,5</b>	729038
<b>DR 16 5x3,5</b>	729009