



Circular Connectors IP68  
Circular Connectors AC 173 click  
**AC 173 REBUP/5 M20**



### Order Info

reference number (ref. no.)	26021
PU	200
EAN	4028012174294

### Type

Type	panel mount socket
connection type	push-in
number of poles	5 pole
colour	black
protection against incorrect plugging	yes

### Electrical Data

rated voltage	500 V
rated current	17.5 A
rated impulse voltage	2.5 kV

### Connection Data

clamping range	0.25 - 1.5 mm <sup>2</sup>
stripping length	12.0 mm
dismantling length	25.0 mm
clamping units per pole	1
lock nut assembly	1.5 Nm
housing hole	M20
pole marking	1-2-3/L-N-E
wall thickness	- 3.0 mm

### Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	60 °C
T <sub>max</sub> component (operation)	125 °C
T <sub>min</sub> component (operation)	-40 °C
IP Code acc. to EN 60529	IP66/IP68/IP69

### Materials

insulator material	PA 6.6
--------------------	--------

<b>flammability rating acc. to UL 94</b>	V-0
--	-----

---

## Approvals

---

<b>acc. to EN 61984</b>	yes
-------------------------	-----

---

## Accessories

---

<b>AC 173 RWZ/5</b>	26060
---------------------	-------

---

<b>AC 173 RVKB</b>	26032
--------------------	-------

---