



Lighting and Housing Connection IP66

LCS 75/ 3-2 PRO

Order Info

reference number (ref. no.)	27303
PU	500
EAN	4028012179169



Type

Type	panel mount terminal block with strain relief
connection type	push-in
number of poles	2 pole
colour	grey
PE-function	yes
strain relief	yes

Electrical Data

rated voltage	400 V
rated current	16 A
rated impulse voltage	2.5 kV

Connection Data

cross-section rating	2.5 mm ²
clamping range	0.5 - 2.5 mm ²
sheathing cable diameter	7.0 - 13.0 mm
type of conductor internal	solid
type of conductor external	fine stranded, stranded, solid
stripping length internal	12.0 mm
stripping length external	17.0 mm
dismantling length	60.0 mm
clamping units per pole	external: 1 / internal: 2
lock nut assembly	0.7 Nm
grommet assembly	3.0 Nm
housing hole	M20
pole marking	L N
wall thickness	0.5 - 2.5 mm
strain relief assembly	↺ 4.0 Nm

Ambient Conditions

T_{max} ambient air (at rated current)	40 °C
T_{min} ambient air (operation)	-20 °C
T_{max} component (operation)	95 °C
IP Code acc. to EN 60529	IP66/IP67/IP68
impact resistance acc. to EN 62262	IK08
ammonia resistance	yes

Materials

insulator material	PA
housing material	PA
gasket material	TPE, NBR
contact material	spring steel, copper
contact plating	tin-plated
flammability rating acc. to UL 94	V-2